


# Manual For Tactical Spec Reflex Sight

## PLEASE READ THE ENTIRE MANUAL

**FAILURE TO FOLLOW THESE INSTRUCTIONS AND PROCEDURES MAY RESULT IN INJURY OR DEATH**

**Always follow firearm safety rules as outlined by the firearms manufacturer. Keep this and all firearm related products locked and secured from children or other unauthorized users**

---

 **WARNING: UNLOAD YOUR FIREARM BEFORE INSTALLING OR REMOVING YOUR SIGHT. FIRST REMOVE THE MAGAZINE FROM THE FIREARM. SECOND, VISUALLY AND MANUALLY CHECK AND CLEAR THE CHAMBER AND ACTION OF AMMUNITION.**

## QUICK START

- Power On: With a battery installed, press and hold either brightness adjustment button(+)(-) to power up the sight to the last used level of intensity.
- Power off: To power down the system, press and hold (-) button for three seconds.



# SPECIFICATIONS

<b>Reticle</b>	4 MOA Single Red Dot
<b>Parallax</b>	≤3'
<b>Eye relief</b>	Unlimited
<b>Magnification</b>	1x
<b>Housing Material</b>	Aluminium
<b>Surface Finish</b>	Matte Black
<b>Adjustment per Click</b>	1 MOA/Click
<b>Windage/Elevation adjustment</b>	±40 MOA
<b>Storage Temperature</b>	-20 ... +70°
<b>Working Temperature</b>	-10 ... +60°
<b>Rainproof</b>	Yes
<b>Shock Resistance</b>	800 g
<b>Battery</b>	1 x CR2032
<b>Battery Life</b>	Up to 2000 Hrs
<b>Brightness Setting</b>	6 levels Daytime and 2 Night Vision
<b>Objective Diameter</b>	21 mm
<b>Weight</b>	0.34 lb/155 g
<b>Dimensions</b>	2.7" x 1.7" x 2.1" / 68 x 42 x 53 mm

## BATTERY REPLACE

You sight is powered by 1 pc of CR2032 battery, should the dot grow dim or not turn on, you will need to replace the battery. Please use the proper coin or screw to unscrew the battery compartment cover. Remove the used battery, insert the new one and screw on the cover again .

Note: The positive(+) size facing inside.

## MOUNTING:

Your sight includes an integrated weaver or dovetail mount that fits weaver and picatinny rail base. For safety reasons, allow at least 3 inches of clearance between the sight and your eyes when shooting .set the mount onto the rail base so that the rail clamp bolt aligns with the crosscut grooves on your rail. Work the rail clamp into the rail until the clamping bolts seats onto the rail. Securely tighten the sight by locking screw with a proper wrench. Do not over tighten the mounting system, it may damage the sight mount.

## ADJUSTING THE BRIGHTNESS LEVEL

There are 6 brightness levels for this sight. To adjust the brightness level of the reticle intensity you simply press the button (+) (-).

Pressing the (+) button will increase the brightness a single step until the maximum level has been achieved.

Press the (-) button will decrease reticle brightness until the minimum level has been reached.

- Auto Off : The sight is equipped with intelligent power management to prolong battery life when not in use. After a period of one hours of inactivity. The sight will automatically enter sleep mode. Pressing either(+)(-) button will wake up the sight to the previously used brightness level.

## Aiming Dot:

The BJ101 possesses a 4MOA round dot for precise aiming. This reticle is approximately 2.5" in diameter at 50 yards. Depending on brightness and ambient conditions the size may appear to change.

## ZEROING/PRECISION ADJUSTMENT

With the sight mounted, set the firearm onto a solid support and aim at target 50 or 100 yards/meters away. Windage is the horizontal (left-to right) adjustment. Its on the right of the sight. Elevation is the vertical (up-to down) adjustment, its on the top of the sight. The sight feature 1 M.O.A. windage and elevation adjustment with audible click, meaning that 1 click moves the point of impact 1 inch at 100 yards. Adjust windage & elevation screw in the direction you want to move the bullet impact.

## LENS CARE

The external optics of the BJ101 are generally resistant to scratches and common firearm cleaning chemicals. periodically the optics may become dirty from normal use. We recommends using the included microfiber cloth for cleaning.

## STORAGE

Avoid storing the sight in hot place, such as the passenger compartments of vehicles on hot days. The high temperature could adversely affect the lubricants and sealants. A vehicle trunk, a gun cabinet or a closet is preferable. Never leave the sight where direct sunlight can enter either the objective lens.

Damage may result from the concentration (burning glass effect)of the sun's rays

## 1 YEAR WARRANTY

We warrants that this product will be free from defects in materials and workmanship for a period of one year from the date of original retail purchase.

## BATTERY WARNINS



**WARNING: KEEP BATTERY AWAY FROM CHILDREN. THERE IS A CHEMICAL BURN HAZARD ASSOCIATED WITH BATTERY.**



**WARNING: IF A NEW OR USED LITHIUM BUTTON/COIN CELL BATTERY IS SWALLOWED OR ENTERS T HE BODY,IT CAN CAUSE SEVERE INTERNAL BURNS AND CAN LEAD TO DEATH IN AS LITTLE AS 2 HOURS. ALWAYS COMPLETELY SECURE THE BATTERY COMPARTMENT. IF THE BATTERY COMPARTMENT DOES NOT CLOSE SECURELY,STOP USING THE PRODUCT, REMOVE THE BATTERY, AND KEEP IT AWAY FROM CHILDREN.IF YOU THINK BATTERY MIGHT HAVE BEEN SWALLOWED OR PLACE INSIDE ANY PART OF THE BODY,SEEK IMMEDIATE MEDICAL ATTENTION.**